

Armoire Collection Showcase

E-6000[®]
Craft Adhesive

Victorian Treasures Materials List

Victorian Treasures

Designed by Michele Nored for Eclectic Products, Inc.

E-6000[®] Craft Adhesive with snip tip
Unfinished wood armoire (8" h x 5.5" w)
Acrylic craft paint (wedgewood green)
2.5" Resin Cherub twins w/wings
2" Cardboard Hat Box
3.5" Doily Hat
1" Felt Teddy Bear
1 pkg. - assorted victorian treasure buttons
Miscellaneous trimmings (ribbons & lace to embellish hat box & hat)
1 - Felt square or other fabric remnant

8.5" x 11" Decorative paper
3/16" x 4.75" Wood dowel
Small gold cord with tassels
1/2 yd. - 2" Wire ribbon
1 - 2" x 3" Oval scalloped edge mirror
Gold wire mesh holiday dress ornament
Other Supplies:
Paint Brush
Scissors
Sand Paper
Acetone
Cotton Swab



Victorian Treasures Materials



1. center resin cherubs to top...



3. ...embellish hat box, hat & bear...



6. ...position to inside doors.



Allow to dry for 24-72 hours @ 70°F.

Directions

Note: Read these directions and the instructions on the opposite side completely before beginning this project.

1. With armoire laying on backside, center resin cherubs to outside-top and secure in place using E-6000. Allow to dry until cherub does not move by gentle touch. Reposition as needed.
2. Paint armoire inside, then outside, being careful not to move cherubs. Paint hat box also. Allow paint to dry to the touch.
3. Meanwhile, embellish hat box, hat & bear - with victorian treasures, miscellaneous trimmings and using E-6000. Adhere bear to top of hat box.
4. Trim felt to 2.5" x 4.625"; trim paper to 5.5" x 10". Position paper before adhering; crease corners. Adhere felt to inside floor & adhere paper to inside walls using E-6000 on all corners & edges. Pull or spread felt and paper to corners and edges.
5. Center and position wood dowel at the top of the inside (like a closet rod). Dowel should fit snugly; sand one end if too snug, until it fits properly. Once dowel is positioned, secure in place using a dab of E-6000 at each end. Keep positioned until E-6000 is dry to a gentle touch.
6. Trim 2" wire ribbon to (2) 6" lengths. Fold each of 4 ends under approx. 1/4". Apply E-6000 to each fold & position to inside doors. Allow to dry to a gentle touch.
7. Meanwhile, using E-6000, adhere hat to upper, left-hand corner of inside wall; adhere hat box with bear to left-hand corner of inside floor; drape-over and adhere gold tassels to left-hand end of dowel; adhere any remaining victorian treasures or trimmings to inside walls, floor and doors; adhere dress ornament to right-hand side of inside; and lastly, with armoire on its backside, adhere mirror to left inside door.
8. Since the doors will primarily be open to showcase the collection, no additional embellishing to the outside of the armoire is necessary. Allow finished project to dry for 24 to 72 hours at 70°F.
9. Use acetone-based solvent on a cotton swab, to remove any unwanted paint on door hinges or unwanted wet

E-6000[®]

INDUSTRIAL STRENGTH CRAFT ADHESIVE

INSTRUCTIONS

1. Please read all directions before using. E-6000[®] should be used in a well-ventilated area.
2. Surface should be clean, dry and free of dirt. For best results, roughen surface before use.
3. Puncture the seal in the neck of the tube using the pointer cap.
4. Test small area before full use.
5. Best when used between 70°F and 85°F.
6. Cure time increases with lower temperatures and decreases with higher temperatures.
7. For maximum strength, allow the bond to dry longer than 48 hours.
8. Keep threads at the neck of the tube free of E-6000[®] residue. To ensure easy cap removal, apply a thin coat of petroleum jelly to the threads of the tube before replacing the cap.
9. Clean uncured adhesive with small amounts of acetone or citrus-based solvents. Cured material may be removed by cutting or scraping.
10. Store unused E-6000[®] at room temperature in a dry area.
11. For further information, call (800) 767-4667.

Always test a small area before full use on any project to ensure proper application technique and dry time.

Note: E-6000[®] May damage finished surfaces. Avoid such contact until E-6000[®] is completely dry.

COMMONLY ASKED QUESTIONS

What temperature range does E-6000[®] withstand?

E-6000[®] can be applied in temperatures ranging from 50°F to 90°F. When cured, E-6000[®] can withstand temperatures between -40°F and 150°F.

How can uncured E-6000[®] be cleaned up?

Small amounts of acetone or citrus-based solvents may be used. E-6000[®] will ball up and brush off.

How can cured E-6000[®] be removed?

Cured E-6000[®] may be removed by cutting or scraping.

How long does E-6000[®] take to dry?

A full cure takes 24 to 72 hours, depending on the surrounding environment. Cure time increases with lower temperatures and decreases with high temperatures.

How can dry time be decreased?

To speed drying time, apply heat using a hand-held hair dryer. Set dryer on low and do not hold directly on E-6000[®].

Can E-6000[®] be dry-cleaned?

No. Dry-cleaning solvent breaks down E-6000[®]. E-6000[®] is washer/dryer safe.

Can E-6000[®] be used on Styrofoam™ ?

No. E-6000[®] is not recommended for use on any polystyrene, polyethylene or polypropylene plastics.

What materials will E-6000[®] adhere to?

E-6000[®] works on virtually any material, including glass, plastic, metal, leather, vinyl, rubber, neoprene, polycarbonate, brick, marble, ABS, PVC, copper, waterproof cloth, aluminum, brass, wood, linoleum, fiberglass, Naugahyde™, porcelain and ceramic.

Is E-6000[®] safe for photographs?

E-6000[®] is photograph-safe and acid-free after a full cure of 24 to 72 hours at 70°F.

CAUTION: Contains perchloroethylene. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful. **WARNING:** This product contains a chemical known to the state of California to cause cancer. Harmful if inhaled or swallowed. May cause dizziness, headache or nausea. Can cause skin and eye irritation. Exposure may cause damage to the kidneys or liver. Cancer agent based on experimental data.

Keep away from heat and flame. Contact with flame or hot surface may produce toxic gases.

Use only with adequate ventilation. To avoid breathing vapor, open all windows and doors to assure fresh air movement during application and drying. When using do not eat, drink, or smoke. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. If swallowed, do not induce vomiting; get medical assistance. In case of eye contact, immediately flush eye with plenty of water for at least 15 minutes. For further health information, contact a poison control center.

KEEP OUT OF THE REACH OF CHILDREN.

CONFORMS TO ASTM D-4236

LIMITED WARRANTY: The manufacturer will not accept liability for more than product replacement.

www.e-6000.com

Made in the U.S.A. by Eclectic Products, Inc. - - Pineville LA 71361

05/04