



Manufactured by:
Eclectic Products, Inc.
Pineville, LA 71361

Made in the USA

800.767.4667 - Technical Services

www.eclecticproducts.com

www.famowood.com

TECHNICAL DATA SHEET

***Famowood® Trowel Grade
Grain Filler***

PRODUCT DESCRIPTION

FAMOWOOD® TROWEL GRADE GRAIN FILLER specifically formulated for hardwood flooring applications, **FAMOWOOD® TROWEL GRADE GRAIN FILLER** is a water-based product used to fill cracks, seams, defects and open grain in hardwood floors. Specialized additives are incorporated to allow smooth applications and the unique thixotropic characteristics enable the product to hold onto the trowel or broad knife. **FAMOWOOD® TROWEL GRADE GRAIN FILLER** is ready with just a quick stir and dries fast. It's superior strength and adhesion won't crack or crumble under pressure and accepts virtually any stain.

PHYSICAL PROPERTIES

| | |
|-----------------------|---|
| Color(s) | Cherry/Dark Mahogany, Fir/Maple, Golden Oak, Natural, Red Oak (5 colors) |
| Density | 14.0 - 15.0 lbs/gal |
| Solids | 74% ± 2% |
| Coverage | 200 - 400 ft ² /gal |
| Storage | Store between 45 and 85 °F (7 and 29 °C) |
| Freeze/thaw stability | Stable up to five freezes; allow product to warm to room temperature before using |
| Shelf life | 1-1/2 years |

DIRECTIONS FOR USE and APPLICATION NOTES

Please read all directions before using. Product is ready to use with one quick stir. Test a small area before full use.

- Step 1** For best adhesion, cracks or defects should be clean and dry.
- Step 2** Use a trowel or broad knife to fill cracks, seams, knots, defects and open grain in hardwood floors.
- Step 3** A thin film will dry within minutes. Lower temperatures require longer drying periods.
- Step 4** When dry, product can be sanded, drilled, planed, sawn, painted, varnished, lacquered, waxed, or shellacked like ordinary wood.
- Step 5** Clean tools while still wet with water or soap with water. If product has dried on tools, use chlorinated solvent or steam.
- Step 6** Close container after each use.

HAZARDS

Before working with this product, read and become familiar with information concerning hazards, proper use and handling. To request an MSDS, please send an e-mail to msds@eclecticproducts.com or call 800.333.9826.

LIMITED WARRANTY

The product is warranted against any defect in materials or workmanship under normal use and service for a period of 180 days after the date of purchase. The product is also warranted under any implied warranties provided under applicable state law, including, without limitation, the implied warranty of merchantability and the implied warranty of fitness for a particular purpose, for a period of 180 days after the date of purchase. This warranty covers only the original buyer of the product. For warranty service, the buyer should contact the store where the product was purchased, or write Eclectic Products, Inc. P.O. Box 4450, Pineville, LA 71360 or call 800.767.4667. This warranty gives you specific legal rights, and you also have other rights, which vary from state to state.